




QRPBuilder

Micro Multi-Band 40m – 20m EFHW Trap kit



First, familiarize yourself with the parts and check for all the components. If a part is missing, please contact us and we will send one. You must use qrpbuilder@gmail.com to request a part.

Parts List


- 2 – Trap PCB
- 1 – Wire end support PCB
- 1 – C1, 68pF, 2KV, C0G SMD capacitor, marked red
- 1 – C2, 150pF, 2KV, C0G SMD capacitor, marked blue
- 2 – T37-6 toroid, yellow
- 1 – 3ft. #26awg magnet wire
- 1 – Ø1/2" x 4.0" clear heatshrink tubing

All of the components mount on the top side of the boards.



Trap assembly

Take extra care to put the correct toroid on the correct trap. Two traps are required for the antenna, referred to as "Trap A" and "Trap B". The traps cannot be interchanged.

- [] On the backside, mark one board A and the other B, with an indelible marker.



- [] Install C1, 68pF, SMD, C0G capacitor on the “A” trap. Capacitor marked “red”
- [] Install C2, 150pF, SMD, C0G capacitor on the “B” trap. Capacitor marked “blue”




Trap “A” will be resonant just below the 20m band, and trap “B” just below the 30m band. If you desire and have the necessary equipment you can tweak the traps by spreading or compressing the turns on the toroids to achieve ideal resonance.

Trap “A” uses a T37-6 (yellow) core wound with 25 turns for “L1” as shown below, with C1, 68pF capacitor.

- [] Cut the 18” of the 26awg wire, and wind it like the graphic, **25 turns**. Every time the wire goes through the center of the core, counts as one turn. Bend the leads down, trim to 1/4” long, and tin the leads prior to soldering and install them to the top of the board. The magnet wire supplied is Thermaleze® brand and will tin easily with a hot soldering iron. *Always tin the leads before trying to solder them in place and you will greatly eliminate any continuity problems.* Do not pull the wires through the holes past where they are tinned. Re-tin if needed.


Theoretical inductance is 1.9uH for 14.000MHz.




Trap "B" uses a T37-6 (yellow) core wound with 24 turns for "L2" as shown below, with C2, 150pF capacitor.

- [] Cut the 18" of the 26awg wire, and wind it like the graphic, 24 turns. Every time the wire goes through the center of the toroid, counts as one turn. Bend the leads down, trim to 1/4" long, and tin the leads prior to soldering and install them to the top of the board. The magnet wire supplied is Thermaleze® brand and will tin easily with a hot soldering iron. *Always tin the leads before trying to solder them in place and you will greatly eliminate any continuity problems.* Do not pull the wires through the holes past where they are tinned. Re-tin if needed.

Theoretical inductance is 1.70uH for 10.000MHz.




- [] Install the lengths of wire through the strain relief holes and solder where indicated below, and solder to the pads shown below.




The user supplies the three wires for the driven element. We recommend stranded #22-24 AWG for this purpose. The lengths shown below are the lengths we tested and work for most locations and deployment schemes. **Don't mix up the traps.** Trap "A" has the 68pF cap. and trap "B" the 150pF cap.

Wire #1 – 32' 6" (9.90m) Wire #2 - 11' 2" (3.40m) Wire #3 - 16' 9" (5.10m)




Route and terminate the end wire as shown below with the supplied End Support.



It is best to test the antenna wire lengths before you install the heat shrink tubing in case adjustments are necessary.

When you are satisfied with the performance, cut a 1.75" long piece of the Ø1/2" heat shrink tubing, slide the heat shrink onto the end of the wire, center it on the trap, and shrink it to the assembly, as shown below. It will *not* be waterproof, but it is designed to protect the trap from mechanical damage in the field and during storage.



This completes the electrical and mechanical assembly.

Schematic:

Use all the normal cautions throwing wires up in the air near power lines.

How the deployed wire is configured depends greatly what you have to work with in terms of support trees and structures. The simplest configuration is the “Sloper”, where the active element runs from the antenna connection of the tuner, up to a tree branch, or top of a tree.

An “L” configuration may work well if you can get the part of the wire from the tuner up to the tree as vertical as possible.


Use a counterpoise, try to lay it out in a straight line, when possible. A 10’ or 20’ length counterpoise will be helpful.

Our tests showed these results using the Micro 40-15m EFHW Half Wave Tuner/SWR Indicator/Antenna in a sloper configuration with 10’ counterpoise, and we recorded the SWR readings with a MFJ-259B as follows:

Wire #1 – 32’ 6” (9.90m) Wire #2 - 11’ 2” (3.40m) Wire #3 - 16’ 9” (5.10m)

7.050 – 1.1:1
7.300 – 1.2:1
10.100 – 1.1:1
14.050 – 1:1
14.300 – 1:1

A feedline choke, as described in the tuner assembly manual, was used at the antenna to eliminate any feedline radiation.



Notes:
